Last DSM Algorithm UPC_EMC Version

11th January 2005

Input Bits

Input Channel	Bit Description
_	
0	CTB Multiplicity
	Bits 0:15 – Multiplicity
1	VTX Information
	Bit 0 – BBC TAC difference in window
	Bit 1 – ZDC TAC difference in window
	Bit 2 – BBC East small-tile ADC sum over threshold
	Bit 3 – BBC West small-tile ADC sum over threshold
	Bit 4 – BBC East large-tile ADC sum over threshold
	Bit 5 – BBC West large-tile ADC sum over threshold
	Bit 6 – ZDC East ADC sum over threshold 0
	Bit 7 – ZDC West ADC sum over threshold 0
	Bit 8 – ZDC East TAC in window
	Bit 9 – ZDC West TAC in window
	Bits 10:13 – Unused
	Bit 14 – ZDC East ADC sum over threshold 1
	Bit 15 – ZDC West ADC sum over threshold 1
2	Unused
3	EMC Information
	Bits 0:1 - Unused
	Bits 2:3 – BEMC high-tower bits
	Bit 4 – back-to-back flag
	Bits 5:8 - Unused
	Bits 9:10 – EEMC high-tower bits
	Bits 11:15 - Unused
4	Miscellaneous Information
	Bit 0 – Blue bunch filled
	Bit 1 – Yellow bunch filled
	Bits 2:15 - Unused
5	FPD Information
	Bit 0 – FPD East ADC sum over threshold 0
	Bit 1 – FPD West ADC sum over threshold 0
	Bits 2:15 - Unused
6	Special Trigger Requests
	Bits 0:2 – selected special trigger request (zero if no request)
	Bits 3:6 – detector number (0:15) of detector making request
	Bits 7:13 – Unused
	Bit 14 – Zero-bias bit
	Bit 15 – Random bit
7	Unused

Registers

Register	Register Description
0	16-bit low threshold for the CTB Multiplicity

1	16-bit medium threshold for the CTB Multiplicity
2	16-bit high threshold for the CTB Multiplicity
3	16-bit low threshold for CTB Multiplicity Window
4	16-bit high threshold for CTB Multiplicity Window

Output Bits

Bit	Description
Bits 0:14	If Bit 15 = 1 – Special Trigger Requests
	Bits 0:2 – Special Trigger request
	Bits 3:6 – Special Trigger detector
	Bit 7 – Random bit
	Bits 8:15 – Unused, set to 1
	Else – Physics Data
	Bits 0:1 – two bits encoding a number between 0 and 3 indicating
	which of three CTB multiplicity thresholds was passed
	Bit 2 – BBC TAC difference in window
	Bit 3 – ZDC TAC difference in window
	Bit 4 – Both BBC small-tile ADC sums over threshold
	Bit 5 – Both ZDC ADC sums over threshold 0
	Bit 6 – Both ZDC TACs in window
	Bit 7 – UPC_EMC bit
	Bit 8 - Zero-bias bit
	Bit 9 - Blue bunch filled AND yellow bunch filled
	Bits 10:11 – BEMC high-tower bits
	Bits 12:13 – EEMC high-tower bits
	Bit 14 – FPD-East OR FPD-West bit set
Bit 15	Flag indicating meaning of bits 0:14
Bits 16:31	Same definitions as bits 0:15

Internal Logic

- The CTB multiplicity is compared to five thresholds whose values are set during RUN configuration (Regs. 0, 1, 2, 3 and 4). The CTB multiplicity is inside the UPC window if it is greater than the threshold set in register 3 and less than the threshold set in register 4.
- The UPC_EMC bit is a combination of the back-to-back bit and the CTB window with vetos provided by the BBC large tiles and the second ZDC threshold:

back-to-back flag

AND CTB multiplicity in window

AND Both ZDC ADC sums not over threshold 1

AND Both BBC large-tile ADC sums not over threshold

- A decision is made to pass Physics Data or a Special Trigger Request to the TCU.
 - 1. The 3 bits of the special trigger request and the random bit are OR'ed together
 - 2. If ANY of these bits is "1" then output bit 15 will be 1, and the special trigger request and the random bit will be passed to the TCU.
 - 3. If NONE of these bits is "1" then output bit 15 will be 0 and any physics data will be passed to the TCU.